VARTA Flashlight F20

15671



Data Sheet



15671 101 111 Type Features (Technical)..... VARTA Flashlight F20 SMD3535 cool white LED Designation..... Push switch (High/Off/Low/Off/Strobe/Off) 3 x AAA battery Battery required..... Tactical operation when light on (Soft touch button 1 pcs LMP SMT3535 cool when light on--High/Low/Strobe) LED..... white LED, CCT 6000K-8000K Reset to High more if off longer than 15secs Slide head to focus beam (spot to flood or flood to Flood 100 lm spot) Luminous intensity Flood Low 50 lm Comfortable handle with knurling pattern Spot High 50 lm Spot Low 15 lm Portable flashlight Eye risk group I High 5 h Run Time..... Low 10 h 1 m (3.3 feet) impact resistant 10,000 Switch cycle life 30 m Range (calculated distance at maximum luminous intensity with an illuminance of 0.25 lux) PC (Polycarbonate) Material..... **PMMA** ABS Silicone Aluminum (All contact parts made of bronze or nickel-plated steel) 93.3 g (without battery) Weight

No publication or circulation of data to third parties without consent of VARTA Consumer Batteries

33 mm

29 mm

129.5 mm

Dimensions

A (Head diameter)

C (Length)

B (Endcap diameter)